



PRODUCT DESCRIPTION

To create our popular Acclaim™, we merged contemporary design, natural-looking LED lighting, and a highly versatile built-in defogger — offering great lighting to make shaving easier than ever and revolutionizing how your guests experience the shower.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and corrosion-resistant glass, suitable for wet locations including showers. Mirror shall have built-in defogger to keep glass clear and uniform light output in frosted areas, using-replaceable LEDs with greater than or equal to 85 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Suitable for wet locations including the shower
- Copper-free, corrosion-resistant DuraMirror™ glass
- Built-in defogger
- Forward-facing task lighting
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- 7-year limited warranty
- Proudly made in the USA

AVAILABLE OPTIONS

- Forward-phase or 0-10V dimming¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 85
- CCT: 3,000 Kelvin
- 756 lumens per foot
- Calculated L₇₀ 50,000-hour LED lifespan
- Maximum 85 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror

¹Minimum order quantity required.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; transformer must be installed in a dry location, NOT behind the mirror and at least 4 feet from a wet environment, but within 25' of the mirror
- LED driver enclosure should be mounted to rigid surface; mounting holes are provided
- Fixture should be controlled by an on/off switch; light and defogger operate together

MODELS

Base Model*	Dimensions	Power Requirements**
ISF-11.75x11.75-DF	11.75"W x 11.75"H x 2.85"D (298mm x 298mm x 72mm)	120/240 VAC, 19W
ISF-11.75x23.75-DF	11.75"W x 23.75"H x 2.85"D (298mm x 603mm x 72mm)	120/240 VAC, 41W
ISF-12.00x28.00-DF-DL***	12"W x 28"H x 4.22"D (305mm x 711mm x 107mm)	120/240 VAC, 45W

*Base model numbers shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

**Defogger specification: 24V. Power requirements included in overall lighted mirror power requirements listed above.

***12"x28" comes standard with a downlight to illuminate a shelf underneath the mirror.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

